



# Aluminum Grating

## I-BAR SWAGE-LOCKED

11/16" Center to Center of Bearing Bars



**11-SI-4**  
Cross Rods 4" C/C



**11-SI-2**  
Cross Rods 2" C/C

### LOAD & DEFLECTION TABLE

Bar Size	Symbol	Approx. Weight psl	Sec. Mod Per Ft. Of Width	SPAN (Length of Bearing Bar)														
				2'-0"	2'-6"	3'-0"	3'-6"	4'-0"	4'-6"	5'-0"								
1" x 1/4"	11-4-44	3.2	0.545	U	1091	698	485	356	273	215	175							
	11-2-44	3.5		D	0.144	0.225	0.324	0.441	0.576	0.729	0.900							
1-1/4" x 1/4"	11-4-54	3.8	0.852	U	1091	727	545	485	436									
		4.2		D	0.115	0.180	0.259	0.353	0.461	0.583	0.720	0.871						
	11-2-54	4.2		D	0.092	0.144	0.207	0.282	0.369	0.467	0.576	0.697	0.720	0.871				
1-1/2" x 1/4"	11-4-64	4.5	1.227	U	1705	1091	758	557	426	337	273	225						
		4.8		D	0.115	0.180	0.259	0.353	0.461	0.583	0.720	0.871						
1-3/4" x 1/4"	11-4-74	5.1	1.670	U	1705	1364	1136	974	852	758	682	620						
		5.4		D	0.092	0.144	0.207	0.282	0.369	0.467	0.576	0.697	0.720	0.871				
	11-2-74	5.4		D	0.077	0.120	0.173	0.235	0.307	0.389	0.480	0.581	0.691	0.811				
2" x 1/4"	11-4-84	5.8	2.182	U	3341	2138	1485	1091	835	660	535	442	371	316	273			
		6.1		D	0.082	0.129	0.185	0.252	0.329	0.417	0.514	0.622	0.741	0.869	1.008			
2-1/4" x 1/4"	11-4-94	6.4	2.761	U	3341	2673	2227	1909	1670	1485	1336	1215	1114	1028	955			
		6.8		D	0.066	0.103	0.148	0.202	0.263	0.333	0.411	0.498	0.592	0.695	0.806	0.922	1.037	
	11-2-94	6.8		D	0.058	0.090	0.130	0.176	0.230	0.292	0.360	0.436	0.518	0.608	0.706	0.819	0.937	
2-1/2" x 1/4"	11-4-104	7.1	3.409	U	4364	2793	1939	1425	1091	862	698	577	485	413	356	273	215	
		7.4		D	0.072	0.113	0.162	0.221	0.288	0.365	0.450	0.545	0.648	0.761	0.882	1.014	1.152	1.458
	11-2-104	7.4		D	0.064	0.100	0.144	0.196	0.256	0.324	0.400	0.484	0.576	0.676	0.784	0.902	1.024	1.296
				U	5523	4418	3682	3156	2761	2455	2209	2008	1841	1699	1578	1381	1227	
				D	0.051	0.080	0.115	0.157	0.205	0.259	0.320	0.387	0.461	0.541	0.627	0.719	0.819	0.937
				U	6818	4364	3030	2226	1705	1347	1091	902	758	646	557	426	337	
				D	0.058	0.090	0.130	0.176	0.230	0.292	0.360	0.436	0.518	0.608	0.706	0.819	0.937	
				C	6818	5455	4545	3896	3409	3030	2727	2479	2273	2098	1948	1705	1515	
				D	0.046	0.072	0.104	0.141	0.184	0.233	0.288	0.348	0.415	0.487	0.564	0.646	0.737	0.833

U = safe uniform load, psf

C = safe concentrated load, plf

D = deflection, inches

E = modulus of elasticity, 10,000,000 psi

F = fiber stress, 12,000 psi

Material: ASTM B-221, 6063 or 6061

**Deflection:** Spans and loads to the right of the bold line exceed 1/4" deflection for uniform load of 100 psf which provides safe pedestrian comfort. These can be exceeded for other types of loads with engineer's approval.

**General:** Loads and deflections are theoretical and based on static loading.

**Finish:** Mill finish unless otherwise specified.

### SI-11 PANEL WIDTH (inches)

Note: Includes 1/4" (1/8" each side) for extended cross rods on swage-locked (SI).

No. of Bars	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
1/4" Bar	1 <sup>3</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>8</sub>	2 <sup>9</sup> / <sub>16</sub>	3 <sup>1</sup> / <sub>4</sub>	3 <sup>15</sup> / <sub>16</sub>	4 <sup>5</sup> / <sub>8</sub>	5 <sup>5</sup> / <sub>16</sub>	6	6 <sup>11</sup> / <sub>16</sub>	7 <sup>3</sup> / <sub>8</sub>	8 <sup>1</sup> / <sub>16</sub>	8 <sup>3</sup> / <sub>4</sub>	9 <sup>7</sup> / <sub>16</sub>	10 <sup>1</sup> / <sub>8</sub>	10 <sup>13</sup> / <sub>16</sub>	11 <sup>1</sup> / <sub>2</sub>	12 <sup>3</sup> / <sub>16</sub>	12 <sup>7</sup> / <sub>8</sub>	13 <sup>9</sup> / <sub>16</sub>
No. of Bars	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39
1/4" Bar	14 <sup>1</sup> / <sub>4</sub>	14 <sup>15</sup> / <sub>16</sub>	15 <sup>5</sup> / <sub>8</sub>	16 <sup>5</sup> / <sub>16</sub>	17	17 <sup>11</sup> / <sub>16</sub>	18 <sup>3</sup> / <sub>8</sub>	19 <sup>1</sup> / <sub>16</sub>	19 <sup>3</sup> / <sub>4</sub>	20 <sup>7</sup> / <sub>16</sub>	21 <sup>1</sup> / <sub>8</sub>	21 <sup>13</sup> / <sub>16</sub>	22 <sup>1</sup> / <sub>2</sub>	23 <sup>3</sup> / <sub>16</sub>	23 <sup>7</sup> / <sub>8</sub>	24 <sup>9</sup> / <sub>16</sub>	25 <sup>1</sup> / <sub>4</sub>	25 <sup>15</sup> / <sub>16</sub>	26 <sup>5</sup> / <sub>8</sub>
No. of Bars	40	41	42	43	44	45													
1/4" Bar	27 <sup>5</sup> / <sub>16</sub>	28	28 <sup>11</sup> / <sub>16</sub>	29 <sup>3</sup> / <sub>8</sub>	30 <sup>1</sup> / <sub>16</sub>	30 <sup>3</sup> / <sub>4</sub>													